

Bright Plus

Product description

Bright Plus is an acrylic Emulsion Based Interior & Exterior Cement Primer water thinnable Paint . It protect the walls from Sunlight , UV rays, Rains,Fungal attack , Growth of moss etc., It acts as a an Exterior Primer & also for Interior application taking care of the problems and acts as a platform for subsequent coats. Has good opacity coverage and flow, no Health Hazard for applicators.

Recommended use

For Interior Walls & Exterior Walls .

Surface preparation

Ensure surface to be painted is free from oil, dust,grease , loose flakes, cracks etc., Apply Areva Paints Sylo-1 & Sylo-2 fillers . Ensure also fungal attack and moss growth are treated before application of Bright Plus multipurpose cement primer paint.

Pre-painting procedure

The surface is cleaned & dry if there are cracks or undulations fill with suitable exterior putty with mixture of sylo-1.

Application method

Brush, Roller and spray for Interior walls .
Brush and spray for Exterior walls.

Thinning / Dilution

Potable water 10-20% of water only.

Drying Time

Touch Dry : 1 Hour .
Hard Dry : 6 Hours

Coverage

90 Sq ft Per Litre Per Coat depending on the surface.

Technical Detail

Shipping

Packing : 20Ltrs, 10Ltrs , 4Ltrs , 1 Ltrs

Safety Features

Do not apply when there is a drop in temperature . Do not over-thin or over extend brush Stir well & strain before use.

Precaution

Store the container with the lid tightly closed in an upright position in a cool,dry place. Keep out of reach of children & away from food, drink. May be harmful if swallowed . In case of emergency seek immediate medical attention. Wear protective Gadgets during application. Use safety equipments like rubber or polythene gloves, safety goggle & face mask..
No added Lead, Mercury or chromium compounds