

## Classic Putty

|                               |  |
|-------------------------------|--|
| <b>Product description</b>    | It is an Emulsion based Acrylic Putty for the Walls. Classic Putty is applied on Plastered walls of the Interiors. Because of its in built nature the putty penetrates small holes, cracks, crevices etc and gives a smooth finish. The retention of dust is very low, because of its smoothness. This putty can also go as a Substitute to Plaster there by saving cost of sand, cement etc., Gives good opacity and Coverage . |
| <b>Recommended use</b>        | Used only for Interior Application.  |
| <b>Surface preparation</b>    | Ensure that the Surface to be painted should be free from loose particles , dust, flakes, oil & grease etc., After addressing the Problems , Surface can be coated with one coat of Areva Paint Waterbase Cement Primer and followed by Classic Putty  |
| <b>Pre-painting procedure</b> | The surface is cleaned & dry if there are cracks or undulations fill with suitable exterior putty with mixture of sylo-1.  |
| <b>Application method</b>     | Classic Putty can be applied with Putty Blade , Spatula etc.,  |
| <b>Thinning / Dilution</b>    | Direct   |
| <b>Drying Time</b>            | 6 - 8 Hours  |
| <b>Coverage</b>               |  |
| <b>Technical Detail</b>       |  |
| <b>Shipping</b>               | Packing : 20 Kg , 5 Kg , 1 Kg  |
| <b>Safety Features</b>        | Do not apply when there is a drop in temperature . Do not over-thin or over extend brush Stir well & strain before use.  |
| <b>Precaution</b>             | Store the container with the lid tightly closed in an upright position in a cool,dry place. Keep out of reach of children & away from food, drink. May be harmful if swallowed . In case of emergency seek immediate medical attention. Wear protective Gadgets during application. Use safety equipments like rubber or polythene gloves, safety goggle & face mask..<br>No added Lead, Mercury or chromium compounds           |