

Product description

Emitop is a unique product which is Polyurethane based emulsion exterior finish which is used as a Top coat on all finish coat which gives added protection to painted surface . This is a Water thinnable top coat paint, provides Exterior protection from Rain , sunlight , UV Rays etc.,

Recommended use

Use as a top coat on all finish coat like Distemper , Interior Emulsions, Exterior Paints, Scratch finish, Dholphur stones etc.,

Surface preparation

Since the finish coat has been applied , just dust the surface and apply a coat of Emitop Top Coats.

Pre-painting procedure

Application method

By Brush , Roller & Spray .

Thinning / Dilution

Direct

Drying Time

Touch Dry : 1 Hours
Hard Dry : 8 Hours

Coverage

150 Sq ft Per Litre Per Coat depending on the surface.

Technical Detail

Shipping

Packing : 20 Kg , 10 Kg , 4 Kg, 1 Kg, 500gm.

Safety Features

Do not apply when there is a drop in temperature . Do not over-thin or over extend brush Stir well & strain before use.

Precaution

Store the container with the lid tightly closed in an upright position in a cool,dry place. Keep out of reach of children & away from food, drink. May be harmful if swallowed . In case of emergency seek immediate medical attention. Wear protective Gadgets during application. Use safety equipments like rubber or polythene gloves, safety goggle & face mask. No added Lead, Mercury or chromium compounds .