



Flex Sheen

Product description

Flex Sheen is a multi Purpose specially designed Acrylic Emulsion water thinnable Interior & Exterior wall finish Paint . It has extra sheen takes care of rain, sunlight , UV rays etc., It is hard on Exterior Walls . It is Eco Friendly with good Opacity , Coverage, with no health hazards and dries faster .

Recommended use

Can be used for Interior & external walls.

Surface preparation

Ensure Surface preparation for both Interior & Exterior Walls are free from oil, grease,dust, cracks,loose flakes, crevices etc., Apply coat of Areva Paints water thinnable Cement primer, f followed by Putty for internal & external and apply 2 coats of Flex Sheen Paint .

Pre-painting procedure

The surface is cleaned & dry if there are cracks or undulations fill with suitable exterior putty with mixture of sylo-1. Apply a coat of idea petal exterior primer & allow it to dry before applying the top coats.

Application method

By Brush , Roller & Spray .

Thinning / Dilution

Potable water 10-20% of water only.

Drying Time

Touch Dry : 1 Hour
Hard Dry : 6 Hours

Coverage

100 Sq ft Per Litre Per Coat depending on the surface.

Technical Detail

Shipping

Packing : 20Ltrs, 10Ltrs , 4Ltrs , 1 Ltrs

Safety Features

Do not apply when there is a drop in temperature . Do not over-thin or over extend brush Stir well & strain before use.

Precaution

Store the container with the lid tightly closed in an upright position in a cool,dry place. Keep out of reach of children & away from food, drink. May be harmful if swallowed . In case of emergency seek immediate medical attention. Wear protective Gadgets during application. Use safety equipments like rubber or polythene gloves, safety goggle & face mask..
No added Lead, Mercury or chromium compounds