



Jointex Powder

Product description

Jointex Powder is one of the main ingredients when mixed with Jointex Sealents in the ratio of 1:1 gives such a product when applied gives such protection that it is not easy to remove, it is a polymer based product where it is very tough, easy to apply.

Recommended use

On Churkey, roof tops, water tanks (non conventional) and surfaces exposed to rain, water, sunlight , UV Rays etc.,

Surface preparation

Ensure the surface to be painted to be free from oil,grease,dust,cracks,crevices etc., Treat the surface clean and dry and apply Jointex Powder, Jointex Sealent in the ratio of 1:1 . Mix only that Quantity that has to be used for immediate usage.

Pre-painting procedure

Application method

By Brush.

Thinning / Dilution

Direct mixing 1:1

Drying Time

Touch Dry : 1/2 an Hour
Hard Dry : 8 Hour

Coverage

35 Sq ft Per Litre Per Coat depending on the surface.

Technical Detail

Shipping

Packing : 20 Kg , 10 Kg , 1 Kg & 1/2 Kg.

Safety Features

Do not apply when there is a drop in temperature . Do not over-thin or over extend brush
Stir well & strain before use.

Precaution

Store the container with the lid tightly closed in an upright position in a cool,dry place. Keep out of reach of children & away from food, drink. May be harmful if swallowed . In case of emergency seek immediate medical attention. Wear protective Gadgets during application. Use safety equipments like rubber or polythene gloves, safety goggle & face mask..
No added Lead, Mercury or chromium compounds