

Product description	Nano Exterior Primer for the Exterior walls is an Emulsion based paint which is water thinnable Cement Primer It protects from Heavy rains , Sunlight , UV Rays , Fungal attack and moss growth etc., It repels rain water, acts and protects the penetration of water into the walls. Has good opacity and coverage.
Recommended use	For all Exterior Walls of the buildings.
Surface preparation	Ensure the surface is free from Oil, dust, Grease , flakes , fungal & moss attack, cracks & crevices .Use Sylo-1 Areva Paints fillers to fill the Cracks & crevices and then apply Nano Exterior Primer one or two Coats.
Pre-painting procedure	The surface is cleaned & dry if there are cracks or undulations fill with suitable exterior putty with mixtur
Application method	By Brush or Spray
Thinning / Dilution	Potable water 10-20% of water only.
Drying Time	<u>Touch Dry</u> : 1 Hour. Hard Dry : 6 Hours .
Coverage	80-90 Sq ft Per Litre Per Coat depending on the surface.
Technical Detail	
Shipping	Packing : 20Ltrs, 10Ltrs , 4Ltrs , 1 Ltrs
Safety Features	Do not apply when there is a drop in temperature . Do not over-thin or over extend brush Stir well & strain before use.
Precaution	Store the container with the lid tightly closed in an upright position in a cool,dry place. Keep out of reach of children & away from food, drink. May be harmful if swallowed . In case of emergency seek immediate medical attention. Wear protective Gadgets during application. Use safety equipments like rubber or polythene gloves, safety goggle & face mask.. No added Lead, Mercury or chromium compounds