



Roof Plaster

Product description

It is a unique product polymerised when applied on Churkey Roof tops gives a very cooling effect to the walls. It is white in colour , it reflects the Sunlight and rays, protects the surface from rain, UV rays etc., It is a very good water proofing product and water thinnable, good opacity , coverage and dries faster.

Recommended use

On all roof tops, churki, sajjas, surface exposed to rain etc.,

Surface preparation

Ensure the surface to be painted is free from oil, grease, dust, flakes, cracks, crevices etc., Ensure safety measure before painting Ruff Top Paint, it is painter friendly and has no Health Hazards.

Pre-painting procedure

The surface is clean & dry if there are cracks or undulations fill it with suitable exterior putty with mixture of Sylo-1. Apply a coat of idea petal exterior primer & allow it to dry before applying the top coats.

Application method

By Brush.

Thinning / Dilution

Potable water 5-10%.

Drying Time

Touch Dry : 1 Hour
Hard Dry : 8 Hour

Coverage

80-100 Sq ft Per Litre Per Coat depending on the surface.

Technical Detail

Shipping

Packing : 20Ltrs, 10Ltrs , 4Ltrs , 1 Ltrs

Safety Features

Do not apply when there is a drop in temperature . Do not over-thin or over extend brush Stir well & strain before use.

Precaution

Store the container with the lid tightly closed in an upright position in a cool, dry place. Keep out of reach of children & away from food, drink. May be harmful if swallowed . In case of emergency seek immediate medical attention. Wear protective Gadgets during application. Use safety equipments like rubber or polythene gloves, safety goggle & face mask.. No added Lead, Mercury or chromium compounds