

Product description	S Plus is a Good Wall finish , with rich in Emulsion resin , very good alternative to Conventional Distemper , Very clean shades , smooth finish , Good Opacity and Coverage . Dries fast paving for second coat the same day by reducing cost of Labour . It is water thinnable Paint for Interior Walls.
Recommended use	For Interior of Walls & Ply wood .
Surface preparation	Ensure that the walls to be primed it should be free from loose particles , dust, flakes, oil & grease etc., Apply one coat of Areva Paints Water based cement Primer and subsequently Putty, followed by 12 coats of S Plus acrylic Emulsion finish Paint.
Pre-painting procedure	The Surface is clean & dry if there are cracks or undulations fill it with shine coat putty / 4X putty & sand it after drying to make the wall smooth . Apply a coat of idea petal / Aqua WTC Primer & allow it to dry before applying the top coats .
Application method	It can be brushed, rolled or sprayed. This product comes not only in white but in different bases & various vibrant colours also .
Thinning / Dilution	Portable Water 10-20% of water only .
Drying Time	<u>Touch Dry</u> : 1/2 an hour . Hard Dry : 6 Hours
Coverage	100 Sq ft Per Litre Per Coat depending on the surface.
Technical Detail	
Shipping	Packing : 20Ltrs, 10Ltrs , 4Ltrs , 1 Ltrs
Safety Features	Do not apply when there is a drop in temperature . Do not over-thin or over extend brush Stir well & strain before use.
Precaution	Store the container with the lid tightly closed in an upright position in a cool,dry place. Keep out of reach of children & away from food, drink. May be harmful if swallowed . In case of emergency seek immediate medical attention. Wear protective Gadgets during application. Use safety equipments like rubber or polythene gloves, safety goggle & face mask.. No added Lead, Mercury or chromium compounds