



Scratch

Product description	Acrylic Emulsion Based with special resins, with Rutile Titanium Di Oxide mixed with minerals size 0.5mm or 1mm in paste form to be applied on Plastered surface of walls, Gives added Protection to the walls , taking care of UV rays , heavy rains, and does not allow water to Penetrate into the walls.
Recommended use	Specially designed for External Walls, Can also be used for Internal Walls.
Surface preparation	Surface to be free from Oil, dust, grease etc., If Cracks on the wall are seen fill it with necessary Crack fillers. If the Surface is slightly rough , it will have good adhesion.
Pre-painting procedure	
Application method	Normally Trowel Application.
Thinning / Dilution	
Drying Time	Advisable for Over night drying because of the Viscous of the Paint .
Coverage	80-90 Sq ft for 30 Kg bag
Technical Detail	
Shipping	Packing : 30 Kg , 20 Kg
Safety Features	Do not apply when there is a drop in temperature . Do not over-thin or over extend brush Stir well & strain before use.
Precaution	Store the container with the lid tightly closed in an upright position in a cool,dry place. Keep out of reach of children & away from food, drink. May be harmful if swallowed . In case of emergency seek immediate medical attention. Wear protective Gadgets during application. Use safety equipments like rubber or polythene gloves, safety goggle & face mask.. No added Lead, Mercury or chromium compounds