



Ultra Enamel

Product description	Water based Enamel Paint to reduce Pollution in the Country designed for all segments of the Society, House hold, Commercial, Industrial, Builders segment. Good flow, Opacity, Coverage and dries faster
Recommended use	For Metals, Wood & Walls for Interior & Exterior Application .
Surface preparation	Ensure that the Surface to be painted is free from loose particles, dust, flakes, Crevices, oil & grease etc, Kindly refer surface preparation details for Metals, Wood & Walls which is exhaustion for different substrates.
Pre-painting procedure	The Surface is clean & dry if there are cracks or undulations fill it with shine coat putty $/$ 4X putty & sand it after drying to make the wall smooth. Apply a coat of idea petal $/$ Aqua WTC Primer & allow it to dry before applying the top coats.
Application method	Can be applied by Brush, Roller or Spray. This product comes not only in white but in different bases & various vibrant colours also.
Thinning / Dilution	Portable Water 10-20% of water only .
Drying Time	Touch Dry: 1 Hour Hard Dry: 12 Hour
Coverage	150 Sq ft Per Litre Per Coat depending on the surface.
Technical Detail	
Shipping	Packing: 20Ltrs, 10Ltrs, 4Ltrs, 1 Ltrs
Safety Features	Do not apply when there is a drop in temperature . Do not over-thin or over extend brush Stir well & strain before use.
Precaution	Store the container with the lid tightly closed in an upright position in a cool, dry place. Keep out of reach of children & away from food, drink. May be harmful if swallowed. In case of emergency seek immediate medical attention. Wear protective Gadgets during application. Use safety equipments like rubber or polythene gloves, safety goggle & face mask No added Lead, Mercury or chromium compounds