



Water Shield

Product description

Water Shield is a Specially designed acrylic emulsion based resins water thinnable exterior paint for the walls. It has very good Opacity , Coverage , flow . Because of its designed structure penetrates holes or cracks, crevices and protects the painted structure from heavy rains, Sunlight , UV Rays etc., It protects from fungal and moss attack . It can be Washed.

Recommended use

For all Exterior Walls application .

Surface preparation

Ensure the surface to be painted is free from oil , Gfrease , dust , cracks , crevices etc., If more cracks are seen treat with Areva Sylo-1 & Sylo-2 fillers. Apply a coat of Areva Paints Exterior water thinnable Primer and then apply 2 coats of Water Shield .

Pre-painting procedure

The surface is cleaned & dry if there are cracks or undulations fill with suitable exterior putty with mixture of sylo-1. Apply a coat of idea petal exterior primer & allow it to dry before applying the top coats.

Application method

By Brush , Exterior Roller & Spray .

Thinning / Dilution

Potable water 10-20% of water only.

Drying Time

Touch Dry : 1 Hour
Hard Dry : 6 Hour

Coverage

120 Sq ft Per Litre Per Coat depending on the surface.

Technical Detail

Shipping

Packing : 20Ltrs, 10Ltrs , 4Ltrs , 1 Ltrs

Safety Features

Do not apply when there is a drop in temperature . Do not over-thin or over extend brush Stir well & strain before use.

Precaution

Store the container with the lid tightly closed in an upright position in a cool,dry place. Keep out of reach of children & away from food, drink. May be harmful if swallowed . In case of emergency seek immediate medical attention. Wear protective Gadgets during application. Use safety equipments like rubber or polythene gloves, safety goggle & face mask.. No added Lead, Mercury or chromium compounds