



Wood Primer

Product description

Wood Primer is alloyed based resin mixed with Mineral Turpentine oil and when applied on Wood takes care of the wood from attacks from cracking, growth of algae, loss of oil from the wood. Takes care from rain , sunlight etc.,

Recommended use

In all construction activities , home, Institutionals etc.,

Surface preparation

Ensure that the wood to be primed is sanded well , treat it with knotting varnish and then apply Wood Primer mixed with Mineral Turpentine Oil for the flow of the Paint.

Pre-painting procedure

Application method

By Brush , Roller & Spray .

Thinning / Dilution

Direct.

Drying Time

Touch Dry : 1 Hour
Hard Dry : 8 Hours

Coverage

100 Sq ft Per Litre Per Coat depending on the surface.

Technical Detail

Shipping

Packing : 20Ltrs, 10Ltrs , 4Ltrs , 1 Ltrs & 500 ML .

Safety Features

Do not apply when there is a drop in temperature . Do not over-thin or over extend brush Stir well & strain before use.

Precaution

Store the container with the lid tightly closed in an upright position in a cool,dry place. Keep out of reach of children & away from food, drink. May be harmful if swallowed . In case of emergency seek immediate medical attention. Wear protective Gadgets during application. Use safety equipments like rubber or polythene gloves, safety goggle & face mask..
No added Lead, Mercury or chromium compounds