



Zinccrome Yellow Primer

Product description

One of the best products in the Industry to avoid formation of rust on metals, because of zinc content it takes extra precaution in arresting the rust formation. It is used in all segments be it Home, Industry, OEM's and Heavy Industries. The paint is a prime coat and should be thinned with Mineral Turpentine oil.

Recommended use

It is used at homes for grills, gates, Industries, OEM's and also Heavy Industry it is better than Red Oxide Metal Primer.

Surface preparation

Ensure the surface to be painted is free from oil, grease, dust, loose flakes, mill scale formation, cracks, holes and crevices. Care to be taken to prepare the surface before painting Zinc crome yellow primer or it will get rusted soon.

Pre-painting procedure

Application method

By Brush, Roller, Spray.

Thinning / Dilution

Direct.

Drying Time

Touch Dry : 1 Hour
Hard Dry : 8 Hours

Coverage

100 Sq ft Per Litre Per Coat depending on the surface.

Technical Detail

Shipping

Packing : 20Ltrs, 10Ltrs, 4Ltrs, 1 Ltrs & 500ML.

Safety Features

Do not apply when there is a drop in temperature. Do not over-thin or over extend brush Stir well & strain before use.

Precaution

Store the container with the lid tightly closed in an upright position in a cool, dry place. Keep out of reach of children & away from food, drink. May be harmful if swallowed. In case of emergency seek immediate medical attention. Wear protective Gadgets during application. Use safety equipments like rubber or polythene gloves, safety goggle & face mask..
No added Lead, Mercury or chromium compounds